

1. Identification

Product identifier SUPER STRIP

Other means of identification

SDS number 576N-66A

Product code HIL00152

Recommended use Stripper

Recommended restrictions For Labeled Use Only
DO NOT USE ON GLASS.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.
St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (800) 365-1555 (Ext. 8206)

Fax (816) 383-8406

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300
(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Hazards of the product as supplied

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 1
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

OSHA defined hazards Not classified.

Other hazards

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information PERSONAL PROTECTIVE EQUIPMENT: For eyes use chemical safety goggles; for skin wear impervious rubber gloves, boots, and aprons where splashing of concentrate is a problem. Wear impervious/slip resistant boots such as Hillyard Stripping Boots while standing in the stripping solution.

Label elements



Signal word Danger

Hazard statement Harmful in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. Harmful if inhaled. May cause respiratory irritation. Harmful to aquatic life.

Precautionary statement**Prevention**

Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Take off contaminated clothing and wash it before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Do not dispose of in storm drain. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS No./Unique ID	%
Butoxyethanol		111-76-2	20 - < 30
Ethanolamine		141-43-5	5 - < 10
Sodium xylene sulfonate		1300-72-7	5 - < 10
POTASSIUM HYDROXIDE		1310-58-3	1 - < 3
Sodium metasilicate		6834-92-0	1 - < 3
Other components below reportable levels			50 - < 60

4. First-aid measures**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Headache. Nausea, vomiting. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures**Suitable extinguishing media**

Alcohol resistant foam. Water Spray or Fog. Powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use water spray to reduce vapors or divert vapor cloud drift. This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3 50 ppm
Ethanolamine (CAS 141-43-5)	PEL	6 mg/m3 3 ppm

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Ethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm
POTASSIUM HYDROXIDE (CAS 1310-58-3)	Ceiling	2 mg/m3

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	IDLH	1.1 % 700 ppm
Ethanolamine (CAS 141-43-5)	IDLH	3 % 30 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3 5 ppm
Ethanolamine (CAS 141-43-5)	STEL	15 mg/m3 6 ppm
	TWA	8 mg/m3 3 ppm
POTASSIUM HYDROXIDE (CAS 1310-58-3)	Ceiling	2 mg/m3

Biological limit values**ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other

Avoid contact with the skin. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Wear impervious/slip resistant boots such as Hillyard Stripping Boots while standing in the stripping solution.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge. Use With Adequate Ventilation.

Thermal hazards

None known.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Colorless to slight amber.
Odor	Mild solvent odor

Odor threshold	Not available
Melting point/freezing point	Not applicable / Not available
Boiling point or initial boiling point and boiling range	213 °F (100.56 °C) Corr.
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Flash point	>200.0 °F (>93.3 °C) Tag Closed Cup
Auto-ignition temperature	Not available
Decomposition temperature	Not available
pH	> 13 - < 14
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	100 % Complete
Partition coefficient (n-octanol/water)	Not available
Vapor pressure	15.83 mm Hg
Density and/or relative density	
Density	8.76 lb/gal
Relative density	1.052 at 77°F
Vapor density	1.764 Air=1
Particle characteristics	Not available.
Other information	
Evaporation rate	<1 Slower than 1 Ethyl ether = 1
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	> 81 - < 86 %
Viscosity	Not available
VOC	33 % Concentrate

10. Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not mix with other chemicals.
Incompatible materials	Strong acids. Strong oxidizing agents. Oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
-------------------	--

Skin contact Causes severe skin burns. Harmful in contact with skin.

Butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Nausea, vomiting. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and central nervous system effects. Harmful in contact with skin.

Product	Species	Test Results
SUPER STRIP		
<u>Acute</u>		
Inhalation		
LC50	Guinea pig	6135135 ppm, 6 Hours
	Mouse	319672.125 mg/l, 4 Hours
		2745 ppm, 7 Hours
	Rat	1765 ppm, 4 Hours

Components	Species	Test Results
Butoxyethanol (CAS 111-76-2)		
<u>Acute</u>		
Oral		
LD50	Rat	470 mg/kg
POTASSIUM HYDROXIDE (CAS 1310-58-3)		
<u>Acute</u>		
Oral		
LD50	Rat	273 mg/kg
Sodium metasilicate (CAS 6834-92-0)		
<u>Acute</u>		
Oral		
LD50	Rat	1280 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity	Harmful to aquatic life.		
Product		Species	Test Results
SUPER STRIP			
Aquatic			
Fish	LC50	Fish	1752.6577 mg/l, 96 hours estimated
Components		Species	Test Results
Butoxyethanol (CAS 111-76-2)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Ethanolamine (CAS 141-43-5)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	114 - 196 mg/l, 96 hours
POTASSIUM HYDROXIDE (CAS 1310-58-3)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Western mosquitofish (Gambusia affinis)	80 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Partition coefficient n-octanol / water (log Kow)			
Butoxyethanol			0.83
Ethanolamine			-1.31
Mobility in soil	No data available.		
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
------------------------------	--

Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D002: Waste Corrosive material [pH ≤2 or ≥12.5, or corrosive to steel] The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

UN number	NA1760
UN proper shipping name	Compound, Cleaning Liquid, (Potassium Hydroxide, Monoethanolamine)
Transport hazard class(es)	
Class	8
Subsidiary hazard	-
Label(s)	8
Packing group	II
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to IMO instruments	Not established.

DOT



15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
Toxic Substances Control Act (TSCA)	One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	POTASSIUM HYDROXIDE (CAS 1310-58-3)
SARA 304 Emergency release notification	Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Not listed.
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
SARA 302 Extremely hazardous substance	Not listed.
SARA 311/312 Hazardous chemical	Yes

Classified hazard categories

Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Butoxyethanol (CAS 111-76-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-17-2014

Revision date 10-07-2026

Version # 05

HMIS® ratings
Health: 3
Flammability: 0
Physical hazard: 0

Disclaimer

No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.

Revision information

Hazard(s) identification: Disposal
Physical & Chemical Properties: Multiple Properties
Toxicological Information: Toxicological Data
Toxicological information: Skin contact